

GENIEMAT™ PMIo6 TYPE PF

PERIMETER ISOLATION STRIP



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat™ PMIo6 Type PF

DESCRIPTION: Flat, resilient, single-ply white polyethylene foam perimeter isolation strip that is used to build a tub around the floor so that no hard surface (floor covering) touches any hard vertical surface (protrusion or wall).

APPLICATION: To be attached at the base of the perimeter wall of the entire subfloor, as well as around the perimeter of any protrusions, prior to unrolling and installing GenieMat™ underlayment products, in order to isolate or break the vibration transmission path between the floor and the wall.

FEATURES AND BENEFITS:

- Reduces noise flanking in acoustic-isolated assemblies.
- Bacteria, fungi, and water resistant.
- Easy to unroll, cut, and install.

DIMENSION: Rollgood: 3" wide, 50' long

SHEET THICKNESS: nom. 6 mm (1/4")

SHEET WEIGHT: 0.035 lbs/ft² (0.17 kg/m²)

ROLL WEIGHT: 2 lbs/roll

COVERAGE: 50 linear ft

LEADTIME: 2-3 weeks after receipt of order

Pliteq Inc. T. 416.449.0049 F. 416.849.0415
1370 Don Mills Road, Unit 300, Toronto, ON M3B 3N7
For inquiries, please email info@pliteq.com

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed thicknesses are nominal in imperial measure.

www.pliteq.com